





Hand nozzle PP, PVDF and stainless steel

- Exact, sensitive measuring
- Higher flow rate
- Higher operational safety due to improved seal



New hand nozzle for sensitive and fast delivery



With three totally new developed FLUX hand nozzles in PP (Polypropylene), PVDF (Polyvinylidene fluoride) and stainless steel (S) you can now deliver many media even faster and easier.

The hand nozzles of PP are suitable for the delivery of acids and alkalis, the hand nozzles in stainless steel are suitable for the delivery of flammable fluids. Beyond that the new hand nozzles PVDF are perfectly suitable for the delivery of concentrated acids.

Of course, a large range of accessories is available for the new hand nozzles such as flow back stop valves and longer outlet tubes.

Special features and benefits:

Less effort

on activating due to the ergonomic lever

Safe handling

Novel swivel joint with rotary balls guarantees absolute tightness even under pressure.

Different outlet nozzles for different applications available

The optimised valve provides for

- easier handling
- sensitive measuring
- higher flow rate
- improved operational safety due to optimised seal

S hand nozzles with Ø 28 mm outlet

DN 19, seal PTFE/FEP	001 12 541
DN 25, seal PTFE/FEP	001 12 542
G 1 A, seal PTFE/FEP	001 12 543
G 1¼ A, seal PTFE/FEP	001 12 544
Ø 28 bore without inlet connector, PTFE seal for connection to hose kits	001 12 549

	The new FLUX hand nozzles are together with our pump kits an unbeatable team. You will find further information on these pre-configured FLUX pump kits in our special brochure.
X	

PP hand nozzles with Ø 22 mm outlet

Image:

Hand nozzle PP

DN 19, seal FKM	001 12 500
DN 21, seal FKM	001 12 502
DN 25, seal FKM	001 12 504
DN 19, seal EPDM	001 12 506
DN 21, seal EPDM	001 12 508
DN 25, seal EPDM	001 12 510

PVDF hand nozzles with Ø 22 mm outlet

DN 19, seal FKM	001 12 501
DN 21, seal FKM	001 12 503
DN 25, seal FKM	001 12 505
DN 19, seal EPDM	001 12 507
DN 21, seal EPDM	001 12 509
DN 25, seal EPDM	001 12 511
DN 19, seal FFKM	001 12 512
DN 21, seal FFKM	001 12 513
DN 25, seal FFKM	001 12 514

FLUX-GERÄTE GMBH Talweg 12 · D-75433 Maulbronn Tel +49 (0)7043 101-0 · Fax +49 (0)7043 101-555 info@flux-pumpen.de · www.flux-pumpen.de